



# The Z-Spray line by LT Rich Products



**Z-Max**



**Intermediate**



**Junior**



**Junior 36**



**Junior 36X4**

## Fertilizer System

**220lb** hydraulic driven granular hopper

Variable spread widths from **3' to 25'**

**Cable** operated Side Deflector Shield

**2ea. 50lb** Fertilizer Trays

**220lb** hydraulic driven granular hopper

Variable spread widths from **3' to 25'**

**Cable** operated Side Deflector Shield

**2 ea. 50lb** Fertilizer Trays

**150lb** hydraulic driven granular hopper

Variable spread widths from **3' to 25'**

**Cable** operated Side Deflector Shield

**2ea. 50lb** Fertilizer Trays

**120lb** hydraulic driven granular hopper

Variable spread widths from **3' to 25'**

**Cable** operated Side Deflector Shield

**2ea. 50lb** Fertilizer Trays

**150lb** hydraulic driven granular hopper

Variable spread widths from **3' to 25'**

**Cable** operated Side Deflector Shield

**N/A**

## Spray System

**60 gallon**  
(2ea. 30 gallon tanks)

**10' spray width**  
(options of 2', 6', 8' or 10')

**75' Hose Reel**

Interchangeable nozzle tips  
(8 AVI tip options)

**5.0 GPM** Liquid Pump  
(optional 7.0 GPM) with  
Constant bypass agitation

**3 Section** Breakaway Boom  
(3 separate Directo-Valves)

**240,000 sq. ft.** production  
per fill (at 1/4 gallon per  
1,000 tips)

**30 gallon**  
(2ea. 15 gallon tanks)

**8' spray width**  
(options of 2', 4', 6' or 8')

**75' Hose Reel**

Interchangeable nozzle tips  
(8 AVI tip options)

**5.0 GPM** Liquid Pump  
(optional 7.0 GPM) with  
Constant bypass agitation

**3 Section** Breakaway Boom  
(3 separate Directo-Valves)

**120,000 sq. ft.** production  
per fill (at 1/4 gallon per  
1,000 tips)

**30 gallon**  
(2ea. 15 gallon tanks)

**8' spray width**  
(options of 2', 4', 6' or 8')

**75' Hose Reel**

Interchangeable nozzle tips  
(8 AVI tip options)

**5.0 GPM** Liquid Pump  
(optional 7.0 GPM) with  
Constant bypass agitation

**3 Section** Breakaway Boom  
(3 separate Directo-Valves)

**120,000 sq. ft.** production  
per fill (at 1/4 gallon per  
1,000 tips)

**24 gallon**  
(2ea. 12 gallon tanks)

**8' spray width**  
(options of 2', 4', 6' or 8')

**15' Coil Hose**

Interchangeable nozzle tips  
(8 AVI tip options)

**5.0 GPM** Liquid Pump  
with Constant bypass agitation

**3 Section** Breakaway Boom  
(3 separate Directo-Valves)

**96,000 sq. ft.** production per  
fill (at 1/4 gallon per 1,000  
tips)

**24 gallon**  
(2ea. 12 gallon tanks)

**8' spray width**  
(options of 2', 4', 6' or 8')

**15' Coil Hose**

Interchangeable nozzle tips  
(8 AVI tip options)

**5.0 GPM** Liquid Pump  
with Constant bypass agitation

**3 Section** Breakaway Boom  
(3 separate Directo-Valves)

**96,000 sq. ft.** production per  
fill (at 1/4 gallon per 1,000  
tips)

## Additional Features

**Speedometer & Pressure Gauge**

**16HP** Twin Cylinder Engine

**Locking Caster System**

**Zero Turn Steering**

**5 gallon** fuel tank

**Speedometer & Pressure Gauge**

**16HP** Twin Cylinder Engine

**Locking Caster System**

**Zero Turn Steering**

**5 gallon** fuel tank

**Speedometer & Pressure Gauge**

**16HP** Twin Cylinder Engine

**Locking Caster System**

**Zero Turn Steering**

**5 gallon** fuel tank

**Speedometer & Pressure Gauge**

**16HP** Twin Cylinder Engine

**Locking Caster System**

**Zero Turn Steering**

**5 gallon** fuel tank

**Speedometer & Pressure Gauge**

**16 HP** Twin Cylinder Engine

**N/A**

**Zero Turn Steering**

**5 gallon** fuel tank

## Dimensions

**52" W X 73" L X 50" H**

**16" Front & 20" Rear Tires**  
(10.5" rear tire width)

**940lbs** (dry weight)

**46" W X 73" L X 50" H**

**16" Front & 20" Rear Tires**  
(10.5" rear tire width)

**890lbs** (dry weight)

**42" W X 73" L X 50" H**

**16" Front & 20" Rear Tires**  
(8" rear tire width)

**850lbs** (dry weight)

**35 1/2" W X 73" L X 50" H**

**13" Front & 18" Rear Tires**  
(7.5" rear tire width)

**776lbs** (dry weight)

**35" W X 70" L X 50" H**

**13" Front & 18" Rear Tires**  
(7.5" rear tire width)

**826lbs** (dry weight)