



The Z-Spray line by LT Rich Products



Z-Max



Intermediate



Junior



Junior 36

Fertilizer System

220lb hydraulic driven granular hopper

Variable spread widths from **3' to 25'**

Cable operated Side Deflector Shield

2ea. 50lb Fertilizer Trays

220lb hydraulic driven granular hopper

Variable spread widths from **3' to 25'**

Cable operated Side Deflector Shield

2 ea. 50lb Fertilizer Trays

120lb hydraulic driven granular hopper

Variable spread widths from **3' to 25'**

Cable operated Side Deflector Shield

2ea. 50lb Fertilizer Trays

120lb hydraulic driven granular hopper

Variable spread widths from **3' to 25'**

Cable operated Side Deflector Shield

2ea. 50lb Fertilizer Trays

Spray System

60 gallon (2ea. 30 gallon tanks)

10' spray width
(options of 2', 6', 8' or 10')

75' Hose Reel

Interchangeable nozzle tips
(**8 AVI tip options**)

5.0 GPM Liquid Pump
(optional 7.0 GPM) with Constant bypass agitation

3 Section Breakaway Boom
(3 separate Directo-Valves)

240,000 sq. ft. production per fill
(at 1/4 gallon per 1,000 tips)

30 gallon (2ea. 15 gallon tanks)

8' spray width
(options of 2', 4', 6' or 8')

75' Hose Reel

Interchangeable nozzle tips
(**8 AVI tip options**)

5.0 GPM Liquid Pump
(optional 7.0 GPM) with Constant bypass agitation

3 Section Breakaway Boom
(3 separate Directo-Valves)

120,000 sq. ft. production per fill
(at 1/4 gallon per 1,000 tips)

30 gallon (2ea. 15 gallon tanks)

8' spray width
(options of 2', 4', 6' or 8')

75' Hose Reel

Interchangeable nozzle tips
(**8 AVI tip options**)

5.0 GPM Liquid Pump
(optional 7.0 GPM) with Constant bypass agitation

3 Section Breakaway Boom
(3 separate Directo-Valves)

120,000 sq. ft. production per fill
(at 1/4 gallon per 1,000 tips)

24 gallon (2ea. 12 gallon tanks)

8' spray width
(options of 2', 4', 6' or 8')

15' Coil Hose

Interchangeable nozzle tips
(**8 AVI tip options**)

5.0 GPM Liquid Pump with Constant bypass agitation

3 Section Breakaway Boom
(3 separate Directo-Valves)

96,000 sq. ft. production per fill
(at 1/4 gallon per 1,000 tips)

Additional Features

Speedometer & Pressure Gauge

16HP Twin Cylinder Engine

Suspension Locking Caster System

Zero Turn Steering

5 gallon fuel tank

Speedometer & Pressure Gauge

16HP Twin Cylinder Engine

Suspension Locking Caster System

Zero Turn Steering

5 gallon fuel tank

Speedometer & Pressure Gauge

16HP Twin Cylinder Engine

Suspension Locking Caster System

Zero Turn Steering

5 gallon fuel tank

Speedometer & Pressure Gauge

16HP Twin Cylinder Engine

Locking Caster System

Zero Turn Steering

5 gallon fuel tank

Dimensions

52" W X 73" L X 50" H

16" Front & 20" Rear Tires
(10.5" rear tire width)

940lbs (dry weight)

46" W X 73" L X 50" H

16" Front & 20" Rear Tires
(10.5" rear tire width)

890lbs (dry weight)

42" W X 73" L X 50" H

16" Front & 20" Rear Tires
(8" or 10.5" rear tire width)

850lbs (dry weight)

35 1/2" W X 73" L X 50" H

13" Front & 18" Rear Tires
(7.5" rear tire width)

776lbs (dry weight)